



Applications









Industry/Logistics Covered car parks

Industrial Zones

Certifications








Spe	cifications (Series lumin	aires)			=
4	Voltage (V)	230V	\longrightarrow	Measures	1.500x84x71mm
Hz	Frecuency (Hz)	50-60Hz	Okg	Weight	1.71Kg
φ	Power factor (Cos fi)	Hasta 0.9			
\bigcirc	Dimming	DALI	- Atc	Operating temperature	-10°C~+35 °C
L O	IP Tightness index	IP65	ф	Flux (lm)	6.534/6.858lm
\L	IK Impact resistance	IK07			
\odot	Body color	White		Electrical isolation	CII
1/1	Diffuser Material	PC-O			
	Body	PC		Lifetime	(L70B50>) 50.000h
		1			
K	Colour temperature	4.000K / 6.500K/4.000K	/		
Ø	CRI Colour rendering index	>80			

Prilux guarantees a ± 10% tolerance in light flux measurements.

Dimensions








References							
	W _{LED}	W	ф	ф	K	À	\longleftrightarrow
521055	60W	57W	7.965/8.364lm	6.534/6.858lm	4.000K / 6.500K	>80	1.500x84x71mm

Photometry







Solutions S



description



Cora Industry LITE is the new standalone lighting control system, which is ideal for any industrial installation. With simple, quick, intuitive installation, Cora Industry Lite represents a turning point in development in the industry, providing renewal, control and full management of lighting in factories and warehouses. It has a built-in light sensor, regulates the flux emitted by the luminaires to compensate for the contribution from natural light and achieves optimal energy use by continually monitoring the light level to adjust the luminaires to the levels set.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es



Info	j
Not suitable for your exposure to uva rays.	



Info	j
Connecteur rapide.	