




Specifications (Series luminaires)

	Voltage (V)	220-240V
	Frecuency (Hz)	50/60Hz
	Power factor (Cos fi)	Hasta $\geq 0,9$
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK08
	Body color	9007
	Diffuser Material	PC-T
	Body	AL IAP
	Colour temperature	3000K-4000K-5000K
	CRI Colour rendering index	>70
	Optical	-
	Higher Hemispheric Flow	max. 9100lm
	Measures	541x191x75mm
	Weight	0.001348Kg
	Inclination	-15° / +15°
	Operating temperature	-
	Flux (lm)	max. 9100lm
	Electrical isolation	CI
	Lifetime	(L70B50>)50.000h
	Efficacy	lm/W


References


	W	ϕ_{LUM}	K
679626	30W	3800lm	3000K
		4000lm	4000K
		4200lm	5000K
	50W	6000lm	3000K
		6500lm	4000K
		7000lm	5000K
	70W	8400lm	3000K
		8700lm	4000K
		9100lm	5000K

Dimensions



Photometry





534222

KIT ADAP. TO POST
50MM AVATAR



501743

ADAP KIT. TO POST
Ø76MM VERSATILE
TECH. RAL9007T



660457

KIT ADAP. A POSTE
Ø33MM DORNA



667357

KIT ADAP. A POSTE
Ø42MM DORNA