


















## Specifications (Series luminaires)

	<b>Electrical isolation</b>	CCI
	<b>Voltage (V)</b>	220-240V
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP66
	<b>IK Impact resistance</b>	IK08
	<b>Body color</b>	RAL9007
	<b>Diffuser Material</b>	PC-T
	<b>Body</b>	AL iap
<b>K</b>	<b>Colour temperature</b>	3000K-4000K
	<b>CRI Colour rendering index</b>	>70
	<b>Measures</b>	529x191x76mm
	<b>Operating temperature</b>	-20°C~+50°C
	<b>Flux (lm)</b>	3800lm
	<b>Lifetime</b>	L70B50 >50.000h

## References

	W	$\phi_{LED}$	$\phi_{LUM}$	K
<b>636322</b>	50W	7100lm	6000lm	4000K
<b>636339</b>	70W	9900lm	8400lm	4000K
<b>637374</b>	50W	7100lm	6000lm	3000K
<b>637381</b>	70W	9900lm	8400lm	3000K
<b>650403</b>	30W	4500lm	3800lm	4000K
<b>651196</b>	100W	13800lm	12550lm	3000K
<b>651202</b>	100W	13800lm	12550lm	4000K
<b>652476</b>	30W	4500lm	3800lm	3000K

## Dimensions



## Photometry