






















## Specifications (Series luminaires)

	<b>Electrical isolation</b>	CCI
	<b>Voltage (V)</b>	220-240V
	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Power factor (Cos fi)</b>	Hasta 0,9
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP66
	<b>IK Impact resistance</b>	IK08
	<b>Body color</b>	9007
	<b>Diffuser Material</b>	PC-T
	<b>Body</b>	AL iap
	<b>Colour temperature</b>	3.000K-4.000K
	<b>CRI Colour rendering index</b>	70cromatica
	<b>Measures</b>	529x191x76mm
	<b>Operating temperature</b>	(-20°C,+50°C)
	<b>Flux (lm)</b>	6000lm
	<b>Lifetime</b>	50.000h
	<b>Lifetime</b>	B50>50000h

## References

	W	$\phi_{LED}$	$\phi_{LUM}$	K
<b>636322</b>	50W	7100lm	6000lm	4.000K
<b>636339</b>	70W	9900lm	8400lm	4.000K
<b>637374</b>	50W	7100lm	6000lm	3.000K
<b>637381</b>	70W	9900lm	8400lm	3.000K

## Dimensions



## Photometry