



| Specifications (Series luminaires)                                                  |                            |                  |  |
|-------------------------------------------------------------------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
|    | Electrical isolation       | CII              |                                                                                     |
|    | Voltage (V)                | 220-240V         |                                                                                     |
|    | Frecuency (Hz)             | 50-60Hz          |                                                                                     |
|    | Power factor (Cos fi)      | Hasta >0,5       |                                                                                     |
|    | Dimming                    | No               |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|    | Bushing type               | G24              |                                                                                     |
|    | IP Tightness index         | IP20             |                                                                                     |
|    | IK Impact resistance       | IK06             |                                                                                     |
|    | Body color                 | White            |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|   | Colour temperature         | 4000K-4000K      |                                                                                     |
|  | CRI Colour rendering index | >80              |                                                                                     |
|  | Opening angle              | 120°             |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|  | Measures                   | 28x28x162mm      |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|  | Operating temperature      | -20°C ~ +40°C    |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|  | Flux (lm)                  | max. 915lm       |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|  | Lifetime                   | (L70B50>)25.000h |                                                                                     |
|  | N° of ignitions            | 12.500           |                                                                                     |
|                                                                                     |                            |                  |                                                                                     |
|  | CEE Energy classification  | E                |                                                                                     |

| References                                                                        |    |        |              |       |                                                                                     |
|-----------------------------------------------------------------------------------|----|--------|--------------|-------|-------------------------------------------------------------------------------------|
|  | W  | $\phi$ | $\phi_{LUM}$ | K     |  |
| 681575                                                                            | 9W | >0,5   | 915lm        | 4000K | 28x28x162mm                                                                         |

| Dimensions |  | Photometry |  |
|------------|-------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------------------------|
|------------|-------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------------------------|

