











## Specifications (Series luminaires)

	<b>Electrical isolation</b>	CIII
	<b>Voltage (V)</b>	24V dcV
	<b>Frequency (Hz)</b>	50-60Hz
	<b>IP Tightness index</b>	IP20
	<b>Colour temperature</b>	2.700K~6.500K/2.700K~6.500K
	<b>CRI Colour rendering index</b>	>90
	<b>Opening angle</b>	120°
	<b>Measures</b>	2.000x10mm
	<b>Strip cutting unit</b>	50mm
	<b>Lifetime</b>	(L70B50>) 50.000h





## Info




>5m less performance ((19,2W/m - 19,2W/m WAS - 24,5W/m). The life time of our LED strips is 50.000h as long as the ambient temperature does not exceed 25°C. To ensure the life of the LED for our strips  $\geq 9.6W$ , it is mandatory to place it on a surface that dissipates the heat they generate.

## References



	W	K			
<b>471077</b>	19,2W	2.700K~6.500K	>90	50mm	2.000x10mm
<b>568708</b>	19,2W	2.700K~6.500K	>90	50mm	2.000x10mm

## Dimensions



On request



## Accessories




**472401**

IMAGINE DUAL RF  
REGULATOR 5-24V  
2X5A




**472432**

IMAGINE DUAL  
AMPLIFIER 5-24V  
2X5A




**242813**

POWER SUPPLY  
60W 24VDC LED  
STRIP



**242820**

POWER SUPPLY  
150W 24VDC LED  
STRIP



**242837**

POWER SUPPLY  
250W 24VDC LED  
STRIP



**473682**

POWER SUPPLY  
60W 24V IP67  
LPV-60-24



**473699**

POWER SUPPLY  
100W 24V IP67  
LPV-100-24



**473705**

POWER SUPPLY  
150W 24V IP67  
LPV-150-24



---

## Accessories

---



---

**501453**

---

POWER SUPPLY  
XLG-200-24-A IP67