



4,8W









9,6W



14,4W

Especificações

 Tensão (V)	24V dc
Hz Frequência (Hz)	50-60
K Temperatura de cor	6.500K
 CRI Índice de repr. cromática	>80
 Angulo de abertura	120°
 Dimensão	5x10
 Fluxo (lm)	503lm
 Isolamento elétrico	III
 Vida	(L70B50>) 50.000h
 L70 B10>(500<I≤1.000mA)	L70 >50.000h

Informacje



Enquanto os estoques durarem



Referências




	ϕ_{LUM}	K			
471084	454lm	2.700K	>80	100mm	5x10
471091	480lm	4.000K	>80	100mm	5x10
471107	496lm	5.000K	>80	100mm	5x10
471114	503lm	6.500K	>80	100mm	5x10
471121	0lm	Rojo	>80	100mm	5x10
471138	0lm	Verde	>80	100mm	5x10
471145	0lm	Azul	>80	100mm	5x10
471152	398lm	Ámbar	>80	100mm	5x10
471169	871lm	2.700K	>80	71mm	5x10
471176	910lm	4.000K	>80	71mm	5x10
471183	960lm	5.000K	>80	71mm	5x10
471190	993lm	6.500K	>80	71mm	5x10
471206	1.423lm	2.700K	>80	50mm	5x10
471213	1.482lm	4.000K	>80	50mm	5x10
471220	1.512lm	5.000K	>80	50mm	5x10
471237	1.568lm	6.500K	>80	50mm	5x10
568715	0lm	2.700K	>80	100mm	5x10
568722	0lm	4.000K	>80	100mm	5x10
568739	0lm	5.000K	>80	100mm	5x10
568746	0lm	6.500K	>80	100mm	5x10
568753	0lm	2.700K	>80	71mm	5x10
568999	0lm	4.000K	>80	71mm	5x10
569019	0lm	5.000K	>80	71mm	5x10
569026	0lm	6.500K	>80	71mm	5x10
569033	0lm	2.700K	>80	50mm	5x10
569040	0lm	4.000K	>80	50mm	5x10
569057	0lm	5.000K	>80	50mm	5x10
569064	0lm	6.500K	>80	50mm	5x10
590136	0lm	3.000K	>80	100mm	25x15
590143	0lm	4.000K	>80	100mm	25x15
590150	0lm	2.700K~4.000K	>80	100mm	25x15



Dimensões



A pedido



Consulte opções de acordo com Imagine

Ima 24v ip65 4.8w

PRILUX



Acessórios

