
















Specifications (Series luminaires)

	Electrical isolation	CII
	Voltage (V)	180-250V
Hz	Frecuency (Hz)	50-60Hz
	Power factor (Cos fi)	Hasta $\geq 0,9$
	Dimming	1-10V
	IP Tightness index	IP20
	Body color	White
	Diffuser Material	PC-O
	Body	AL
K	Colour temperature	3.000K/6.500K
	CRI Colour rendering index	>80
	Opening angle	120°
	Measures	225x30mm
	Mounting position	Empotrar
	Operating temperature	-5°C~+35 °C
	Flux (lm)	2.339lm
	Lifetime	(L70B50>) 50.000h




References



	ϕ_{LUM}	K		\odot		\leftrightarrow	
381413	20W	2.198lm	3.000K	>80	Grey 9006	200-210	225x30mm
381420	20W	2.339lm	4.000K	>80	Grey 9006	200-210	225x30mm
381437	20W	2.198lm	3.000K	>80	White	200-210	225x30mm
381444	20W	2.249lm	4.000K	\geq 80	White	\varnothing 200-210	\varnothing 225x30mm
408202	20W	2.488lm	5.000K	>80	White	200-210	225x30mm
408219	20W	2.556lm	6.500K	>80	White	200-210	225x30mm
527293	20W	2.339lm	4.000K	>80	White	200-210	225x30mm
532143	20W	2.339lm	4.000K	>80	White	200-210	225x30mm
543071	2.249lm	4.000K	>80	White	200-210	225x30mm	Yes

Dimensions



Photometry



On request



Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos



Dali

Accessories



387583

SURFACE
ACCESSORY CL
KENTAU 20W WHITE



532181

DRIVER KENTAU
20W 1-10V



Technologies



CELLTECH



CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.



Solutions

S



CTE Pack

description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.



CLASSROOMS Pack

description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.



BLUETOOTH Pack

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es