




| Specifications (Series luminaires)                                                  |                            |                   |  |
|-------------------------------------------------------------------------------------|----------------------------|-------------------|-------------------------------------------------------------------------------------|
|    | Electrical isolation       | CII               |                                                                                     |
|    | Voltage (V)                | 220-240V          |                                                                                     |
|    | Frequency (Hz)             | 50-60Hz           |                                                                                     |
|    | Power factor (Cos fi)      | Hasta >0,7        |                                                                                     |
|    | Dimming                    | No                |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|    | IP Tightness index         | IP65              |                                                                                     |
|    | IK Impact resistance       | IK10              |                                                                                     |
|    | Body color                 | White             |                                                                                     |
|    | Diffuser Material          | PC                |                                                                                     |
|    | Body                       | ABS               |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|  | Colour temperature         | 3000K-4000K-6500K |                                                                                     |
|  | CRI Colour rendering index | >80               |                                                                                     |
|  | Opening angle              | 55°               |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|  | Measures                   | 325x325x80mm      |                                                                                     |
|  | Mounting position          | Superficie        |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|  | Operating temperature      | -20°C ~ +40°C     |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|  | Flux (lm)                  | max. 2481lm       |                                                                                     |
|                                                                                     |                            |                   |                                                                                     |
|  | Lifetime                   | (L70B50>)50.000h  |                                                                                     |

References

|               | W   | $\phi_{LUM}$ | K     |       |     |                  |     |              |
|---------------|-----|--------------|-------|-------|-----|------------------|-----|--------------|
| <b>680387</b> | 12W | 2443lm       | 3000K | White | >80 | (L70B50>)50.000h | 55° | 325x325x80mm |
|               | 16W | 2469lm       | 4000K |       |     |                  |     |              |
|               | 20W | 2481lm       | 6500K |       |     |                  |     |              |

Dimensions



Photometry

