



Applications



Historic buildings



Cultural spaces












Facades








Fairgrounds

Specifications (Series luminaires)




 Voltage (V)	110-240 acV
Hz Frecuency (Hz)	50/60Hz
Φ Power factor (Cos fi)	Hasta $\geq 0,9$
 Dimming	No
 IP Tightness index	IP66
 IK Impact resistance	IK08
 Body color	9007
 Diffuser Material	PC
 Body	AL
K Colour temperature	3000K-4000K
 CRI Colour rendering index	>80
 Higher Hemispheric Flow	max. 3365lm

 Measures	1.000x38x96mm
 Operating temperature	-30°C ~ +50°C
 Surges protection	No
Φ_{LUM} Flux (lm)	max. 3365lm
 Electrical isolation	CI
 Lifetime	(L70B50>)50.000h



Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions




References



	W	ϕ_{LUM}	ϕ/W	
693905	42W	3365lm	80lm/W	No
693912	42W	3365lm	80lm/W	No

Accessories



705035

CONECTOR WC
AUTOBLOCANTE
MACHO/HEMBRA 3P

715263

MG-XTREM H07 RN-F
3G1 450/750 CORTE 1
METRO