





Applications




Classrooms



Health care



Offices




Large surfaces



Home



Hotels



















Restaurants



Retail


Specifications (Series luminaires)



 Voltage (V)	220-240V	 Measures	1.205x57x76mm
Hz Frecuency (Hz)	50/60Hz	 Weight	0.00212Kg
 Current (A)	max.500mA	 Mounting position	Surface Wall,Suspended
 Power factor (Cos fi)	Hasta >0,9	 Operating temperature	-20°C ~ +45°C
 Dimming	No	 Flux (lm)	max. 3350lm
 IP Tightness index	IP20	 Electrical isolation	CI
 IK Impact resistance	IK02	 Lifetime	L70>50000h
 Diffuser Material	PC		
 Body	AL		
K Colour temperature	3000K-4000K		
 CRI Colour rendering index	>80		

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions





References



	W		ϕ_{LUM}	Δ	K		
628013	32W	500mA	3350lm	100°	3000K 4000K	1.205x57x76mm	>80
650366	32W	500mA	3350lm	100°	3000K 4000K	1.205x57x76mm	>80


On request



Emergency kit 3h (mod. 1x/2x
1.200mm/1.500mm)



Dali



662895

ACCESORIO DE SUSPENSION LYNX PRO



662901

ACC. DE SUSPENSION CON ALIMENTACION LYNX




700269

ACCESORIO CONEXION LINEAL ADOSADO LYNX PRO




700276

ACCESORIO CONEXION LINEAL SUSPENSION LYNX



700283

ACCESORIO CONEXION L LYNX PRO OPAL R9016



700306

ACCESORIO CONEXION X LYNX PRO OPAL+PRISM



700320

ACCESORIO CONEXION T LYNX PRO OPAL+PRISM




700344

ACCESORIO ANCLAJE A PARED LYNX PRO R9016



662918

ACC. DE SUSPENSION CON ALIMENTACION LYNX



700290

ACCESORIOS CONEXION L LYNX PRO OPAL+PRISM



700313

ACCESORIO CONEXION X LYNX PRO OPAL+PRISM



700337

ACCESORIO CONEXION T LYNX PRO OPAL+PRISM



700443

ACCESORIO ANCLAJE A PARED LYNX PRO R9005T