

















Specifications (Series luminaires)

	Electrical isolation	CII
	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Power factor (Cos fi)	Hasta $\geq 0,5$
	Dimming	Yes
	IP Tightness index	IP20
	Body color	White
	Body	PC
K	Colour temperature	3.000K/4.000K
	CRI Colour rendering index	>80
	Opening angle	38°
	Measures	Ø90x44mm
	Mounting position	Empotrar
	Inclination	25°
	Flux (lm)	677lm
	Lifetime	(L70B50>) 25.000h



References



	W	ϕ_{LUM}	K					
545488	6,5W	542lm	3.000K	≥ 80	White	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545495	6,5W	573lm	4.000K	≥ 80	White	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545501	6,5W	542lm	3.000K	≥ 80	Grey 9006	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545518	6,5W	573lm	4.000K	≥ 80	Grey 9006	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
580229	7W	677lm	3.000K	> 80	White	70mm	$\phi 90 \times 48 \text{mm}$	No
580236	7W	739lm	4.000K	> 80	White	70mm	$\phi 90 \times 48 \text{mm}$	No
580243	7W	677lm	3.000K	> 80	Grey 9006	70mm	$\phi 90 \times 48 \text{mm}$	No
580250	7W	739lm	4.000K	> 80	Grey 9006	70mm	$\phi 90 \times 48 \text{mm}$	No
587563	7W	677lm	3.000K	> 80	White	70mm	$\phi 90 \times 44 \text{mm}$	Yes
587570	7W	739lm	4.000K	> 80	White	70mm	$\phi 90 \times 44 \text{mm}$	Yes
587587	7W	677lm	3.000K	> 80	Grey 9006	70mm	$\phi 90 \times 44 \text{mm}$	Yes
587594	7W	739lm	4.000K	> 80	Grey 9006	70mm	$\phi 90 \times 44 \text{mm}$	Yes

Dimensions



Photometry

