
















Specifications

	Voltage (V)	220-240V ac
Hz	Frecuency (Hz)	50-60
	Dimming	Yes
	IP Tightness index	20
	Body color	9006
	Body	PC
K	Colour temperature	3.000K
	CRI Colour rendering index	>80
	Opening angle	38°
	Measures	Ø90x48
	Mounting position	Empotrar
	Inclination	25°
	Flux (lm)	677lm
	Electrical isolation	II
	Lifetime	(L70B50>) 25.000h




References



	W	K				
545488	6,5W	3.000K	White	Ø74	Ø90x44	Yes
545495	6,5W	4.000K	White	Ø74	Ø90x44	Yes
545501	6,5W	3.000K	Grey 9006	Ø74	Ø90x44	Yes
545518	6,5W	4.000K	Grey 9006	Ø74	Ø90x44	Yes
580229	7W	3.000K	White	70mm	Ø90x48	Yes
580236	7W	4.000K	White	70mm	Ø90x48	Yes
580243	7W	3.000K	Grey 9006	70mm	Ø90x48	Yes
580250	7W	4.000K	Grey 9006	70mm	Ø90x48	Yes
587563	7W	3.000K	White	70mm	Ø90x44	Yes
587570	7W	4.000K	White	70mm	Ø90x44	Yes
587587	7W	3.000K	Grey 9006	70mm	Ø90x44	Yes
587594	7W	4.000K	Grey 9006	70mm	Ø90x44	Yes

Dimensions



Photometry

