



















Specifications (Series luminaires)

	Electrical isolation	CII
	Voltage (V)	100-240V
Hz	Frecuency (Hz)	50-60Hz
	Power factor (Cos fi)	Hasta $\geq 0,5$
	Dimming	No
	IP Tightness index	IP20
	Body color	9006
	Diffuser Material	PC-T
	Body	AL
K	Colour temperature	3.000K/4.000K
	CRI Colour rendering index	≥ 80
	Opening angle	35°
	Measures	Ø90x44mm
	Mounting position	Empotrado Techo
	Inclination	25°
	Operating temperature	-5 +35
	Flux (lm)	542lm
	Lifetime	(L70B50>)15.000h



References



	W	ϕ_{LUM}	K					
545525	6,5W	542lm	3.000K	≥ 80	White	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545532	6,5W	573lm	4.000K	≥ 80	White	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545549	6,5W	542lm	3.000K	≥ 80	Grey 9006	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
545556	6,5W	573lm	4.000K	≥ 80	Grey 9006	$\phi 74$	$\phi 90 \times 44 \text{mm}$	No
580267	7W	677lm	3.000K	> 80	White	70 x 70	$\phi 90 \times 48 \text{mm}$	No
580274	7W	739lm	4.000K	> 80	White	70 x 70	$\phi 90 \times 48 \text{mm}$	No
580281	7W	677lm	3.000K	> 80	Grey 9006	70 x 70	$\phi 90 \times 48 \text{mm}$	No
580298	7W	739lm	4.000K	> 80	Grey 9006	70 x 70	$\phi 90 \times 48 \text{mm}$	No
587600	7W	677lm	3.000K	> 80	White	70 x 70	90x90x44mm	Yes
587617	7W	739lm	4.000K	> 80	White	70 x 70	90x90x44mm	Yes
587624	7W	677lm	3.000K	> 80	Grey 9006	70 x 70	90x90x44mm	Yes
587631	7W	739lm	4.000K	> 80	Grey 9006	70 x 70	90x90x44mm	Yes

Dimensions



Photometry

