
















## Specifications (Series luminaires)



	<b>Voltage (V)</b>	220-240V
	<b>Frecuency (Hz)</b>	50/60Hz
	<b>Power factor (Cos fi)</b>	Hasta >0.9
	<b>Dimming</b>	DALI
	<b>IP Tightness index</b>	IP65
	<b>IP installed Sealing rating</b>	65
	<b>Diffuser Material</b>	PMMA
	<b>Body</b>	FE
	<b>Colour temperature</b>	4.000K-4.000K
	<b>CRI Colour rendering index</b>	80cromatica
	<b>Opening angle</b>	120°
	<b>Measures</b>	295X1195mm
	<b>Flux (lm)</b>	4315lm
	<b>Electrical isolation</b>	CII
	<b>Lifetime</b>	50.000
	<b>Lifetime</b>	(L70B50>) 50.000h





## References



	W			$\phi_{LED}$	$\phi_{LUM}$	K		
<b>622974</b>	40W	1000mA	>0.9	5600lm	4315lm	4.000K	575X575	No
<b>627849</b>	40W	1000mA	>0.9	5600lm	4315lm	4.000K	575X575	Yes
<b>628761</b>	40W	1000mA	>0.9	5600lm	4315lm	4.000K	275X1175	No
<b>629058</b>	40W	1000mA	>0.9	5600lm	4315lm	4.000K	275X1175	Yes

## Dimensions



## Photometry





---

**On request**

---



Emergency kit

---