
















Specifications (Series luminaires)

	Electrical isolation	CII
	Voltage (V)	230V
Hz	Frecuency (Hz)	50-60Hz
	IP Tightness index	IP20
	Body color	White
	Diffuser Material	PC-O
	Body	AL
K	Colour temperature	3.000K-6.500K
	Opening angle	160°
	Measures	1.185x24x38mm
	Mounting position	Superficie
	Linkable	Si
	Power supply	Incluida
	Flux (lm)	1.925lm
	Lifetime	(L70B50->) 30.000h




References



	W	ϕ_{LUM}	K		\leftrightarrow	
548564	4W	413lm	3.000K	White	325x24x38mm	Yes
548571	4W	450lm	4.000K	White	325x24x38mm	Yes
548588	4W	450lm	6.500K	White	325x24x38mm	Yes
548595	10W	930lm	3.000K	White	585x24x38mm	Yes
548601	10W	1.020lm	4.000K	White	585x24x38mm	Yes
548618	10W	1.020lm	6.500K	White	585x24x38mm	Yes
548625	14W	1.370lm	3.000K	White	885x24x38mm	Yes
548632	14W	1.460lm	4.000K	White	885x24x38mm	Yes
548649	14W	1.460lm	6.500K	White	885x24x38mm	Yes
548656	18W	1.830lm	3.000K	White	1.185x24x38mm	Yes
548663	18W	1.925lm	4.000K	White	1.185x24x38mm	Yes
548670	18W	1.925lm	6.500K	White	1.185x24x38mm	Yes
548687	23W	2.378lm	3.000K	White	1.498x24x38mm	Yes
548694	23W	2.430lm	4.000K	White	1.498x24x38mm	Yes
548700	23W	2.430lm	6.500K	White	1.498x24x38mm	Yes

Dimensions



Photometry





Accessories



548717

SLIMLINE LED
AVANT
ACCESSORIES KIT