



MADE IN SPAIN
Desing by PRILUX



Applications



Offices



Retail



Home



Large surfaces



Hotels





Restaurants




Certifications








Specifications




	Voltage (V)	220-240
Hz	Frecuency (Hz)	50-60
	Current (A)	750mA

	Measures	0
	Mounting position	Superficie/Suspendido
	Inclination	+135°/-135°+90°/-90°

	IP Tightness index	20
	Body color	Black
	Diffuser Material	VT
	Body	AL
	Reflector	AL AN

	Flux (lm)	3.761
	Electrical isolation	CI

K	Colour temperature	4.000K
	CRI Colour rendering index	>80
	Optical	[object Object]



Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References



	W	W		ϕ_{LED}	ϕ_{LUM}	Δ	K
205375	28W	32W	750mA	3.34	3.573	30°	3.000K
205382	28W	32W	750mA	3.515	3.761	30°	4.000K
205399	13W	16W	380mA	1.997	2.137	30°	3.000K
205405	13W	16W	380mA	2.102	2.249	30°	4.000K
205412	28W	32W	750mA	3.34	3.573	30°	3.000K
205429	28W	32W	750mA	3.515	3.761	30°	4.000K
205436	13W	16W	380mA	1.997	2.137	30°	3.000K
205443	13W	16W	380mA	2.102	2.249	30°	4.000K

Photometry

