



MADE IN SPAIN
Desing by PRILUX



Applications



Offices



Retail



Home



Large surfaces



Hotels





Restaurants




Certifications










Specifications





 Voltage (V)	220-240
Hz Frecuency (Hz)	50-60
 Current (A)	380mA

 Measures	0
 Mounting position	Superficie/Suspendido
 Inclination	+90°-90°+135°-135°

 IP Tightness index	20
 Body color	Black
 Diffuser Material	VT
 Body	AL
 Reflector	AL AN

 Flux (lm)	2.075
 Electrical isolation	CI



K Colour temperature	3.000K
 CRI Colour rendering index	>80
 Optical	[object Object]

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W	W		ϕ_{LED}	ϕ_{LUM}	Δ	K
205276	28W	32W	750mA	3.225	3.45	0°	3.000K
205283	28W	32W	750mA	3.394	3.632	0°	4.000K
205306	13W	16W	380mA	1.939	2.075	0°	3.000K
205313	13W	16W	380mA	2.041	2.184	0°	4.000K
205337	28W	32W	750mA	3.225	3.45	0°	3.000K
205344	28W	32W	750mA	3.394	3.632	0°	4.000K
205351	13W	16W	380mA	1.939	2.075	0°	3.000K
205368	13W	16W	380mA	2.041	2.184	0°	4.000K
535540	13W	16W	380mA	1.939	2.075	0°	3.000K
535557	13W	16W	380mA	1.939	2.075	0°	3.000K
535564	13W	16W	380mA	2.041	2.184	0°	4.000K
535571	13W	16W	380mA	2.041	2.184	0°	4.000K
535588	28W	32W	750mA	3.225	3.45	0°	3.000K
535595	28W	32W	750mA	3.225	3.45	0°	3.000K
535601	28W	32W	750mA	3.394	3.632	0°	4.000K
535618	28W	32W	750mA	3.394	3.632	0°	4.000K

Photometry

