




ENOLA SQUARE M

outdoor LED surface-mounted ceiling light anthracite

The ENOLA SQUARE and ROUND light series have a purist style, consisting of a cylindrical or square aluminium construction fitted with powerful LEDs. Thanks to the integrated CCT switch, the light colour can be altered between 3000 K and 4000 K on installation. Thanks to the integrated LED driver, the electrical connection for the light is made directly to the 230 V mains voltage. In order to cover as wide a range of applications as possible, you can opt for one or two-lamp wall lights or ceiling lights in round or square form and in different sizes. This light contains integrated LED light bulbs.



TECHNICAL DATA

Item no.	1003421
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Lumen	840 / 960 lm
Colour temperature	3000/4000 Kelvin
Beam angle	38 °
Color	anthrazit
CRI	90
Service life	30000 h
Risk Group	1
Length	10 cm
Width	10 cm

916566	

Accessories

1005206	ENOLA M , lens asym-metric
1003479	Spacer set , for the ENO-LA SQUARE OUT and ROUND OUT ceiling lights in anthracite
1005205	ENOLA M , lens 20°
1005207	ENOLA M , reflector 60°

Height	12.5 cm
Net weight	0.819 kg
Gross weight	0.978 kg
BIG WHITE Page	831