




L-LINE OUT WL

Outdoor LED wall-mounted light anthracite CCT switch 3000/4000 K

With its linear light variety, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members speak a common language of form, encapsulated in the clean lines of the letter "L". As far as lighting technology is concerned, there are no compromises: the CCT switch for easy selection of light colour temperature (3000 or 4000 K) prior to installation), the straightforward installation process, and a protection rating of IP 65 are just some of the features that make the L-LINE OUT surface-mounted wall light a winner.



TECHNICAL DATA

Item no.	1003539
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Lumen	500/570 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	80
Service life	30000 h
Risk Group	0
Width	15 cm
Height	10 cm

916406	

Depth	10 cm
Net weight	1.024 kg
Gross weight	1.237 kg
BIG WHITE Page	921