




NUMINOS® M | CL, PHASE

NUMINOS® M CL, PHASE, Surface-mounted ceiling light, 3000 K, 14 Watt, trailing edge, 36°, matt black

The NUMINOS® M SPOT surface-mounted ceiling luminaire is designed for indoor use and is particularly suitable for accent lighting in residential and work areas. It features a cylindrical design with a matte black finish. With a power consumption of 14 watts, it delivers a luminous flux of 1800 lumens at a colour temperature of 3000 Kelvin and a beam angle of 36 degrees. The housing is made of aluminium and polycarbonate, ensuring a robust and durable construction. The luminaire is equipped with phase-cut dimming and has an IP20 protection rating. With a product length of 18.5 cm, a diameter of 8.5 cm, and a height of 16.5 cm, it offers compact dimensions for versatile mounting options.



Light source

2093861	A G D

Item no.	1004203
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper