


NUMINOS® S 3Ph.

DALI, 3~ Spotlight, cylindrical, 4000 K, 7.8 Watt, DALI, 24°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1100 lm and an impressive efficiency of 141.03 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004382
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	200
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	166
Number of luminaires at LS C16A	187
Level of inrush current	2.425 A
Duration of inrush current	202 µs
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	24 °
Color	white/black
CRI	90
Service life	50000 h

Light Source

1411582	

Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.579 kg
Gross weight	0.897 kg
BIG WHITE Page	629