


NUMINOS® M 3Ph.

DALI, 3~ Spotlight, cylindrical, 4000 K, 13 Watt, DALI, 36°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1950 lm and an impressive efficiency of 150 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004479
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	94
Number of luminaires at LS C16A	94
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Lumen	1950 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	matt white/matt black
CRI	90
Service life	50000 h

1411588	

Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.833 kg
Gross weight	1.147 kg
BIG WHITE Page	631