


NUMINOS® L | CL, DALI

NUMINOS® L CL, DALI, Surface-mounted ceiling light, 2700 K, 19 Watt, DALI, 60°, matt white / matt black

The NUMINOS® L SPOT is a surface-mounted ceiling luminaire characterised by its cylindrical shape and round canopy. It is designed for indoor use and is particularly suitable for general and accent lighting. The luminaire delivers a luminous flux of 2300 lumens with a colour temperature of 2700 K and a beam angle of 60°, providing a pleasant, directed light distribution. The housing is made of aluminium and polycarbonate, ensuring a robust and durable construction. With a power consumption of 19 watts and DALI 2 dimming technology including touch control, it offers flexible control options. The luminaire has an IP20 rating and a declared service life of 50,000 hours. Its dimensions are 21.3 cm in length, 10 cm in diameter, and 18 cm in height.



Light source

2093865	A G D

Item no.	1004584
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALITouch
Number of through-wires	94
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	60°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper