




OCULUS | PD, single, PHASE

OCULUS PD, Indoor LED pendant light single black DIM-TO-WARM 2000-3000 K

With a high colour rendering index (CRI >90) and the option of dim-to-warm dimming for an especially warm light (2000-3000 K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



Light source

916608	A F

Item no.	1004672
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Level of inrush current	13 A
Duration of inrush current	8 µs
Beam angle	100°
Color	black
CRI	90
LXXBXX data	L70B50
Service life	25 000 h
Risk Group	1
Height	9 cm
Diameter	9 cm
Net weight	0.66 kg
Gross weight	0.79 kg
BIG WHITE Page	257