




# OVALISK WL Sensor

**Outdoor LED ceiling-mounted light anthracite CCT switch 3000/4000 K**

Genuine glass and a perfectly-shaped design with a playful touch thanks to the combination of different materials and shapes used: the lights of the OVALISK family are modern eye-catchers that will look at home in the outdoor area of any sophisticated home or restaurant. OVALISK doesn't just shine with its high-quality appearance-it will also win you over with its easy installation and variable light colour (3000/4000 K), which can be selected via CCT switch. And thanks to a high IP protection rating of 65, OVALISK is also perfectly protected from the elements. And let's not forget the LED sensor in anthracite, which reliably detects every movement. The light duration and sensitivity can be adjusted individually.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1004679 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Number of through-wires** | 19 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | I |
| **Wattage** | 9.6 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 74 |
| **Number of luminaires at LS C16A** | 19 |
| **Level of inrush current** | 15 A |
| **Duration of inrush current** | 100 µs |
| **Temperature at glass (light emission)** | 37 °C |
| **Lumen** | 580/630 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Color** | anthracite |
| **CRI** | 80 |

| | |
|---|---|
| 916555 |  |

| | |
|---|---|
| **Service life** | 30000 h |
| **Risk Group** | 1 |
| **Height** | 28.5 cm |
| **Depth** | 17.8 cm |
| **Diameter** | 17 cm |
| **Net weight** | 2.051 kg |
| **Gross weight** | 2.992 kg |
| **BIG WHITE Page** | 895 |