



NUMINOS® XS | DL

NUMINOS® XS, black / white recessed ceiling light, 3000 K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

798303	A F

Item no.	1005524
Lamps included	No
IP Code	IP20/IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	55°
Color	black/white
CRI	90
UGR ≤	25
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	2
Height	4.5 cm
Diameter	6.5 cm
Net weight	0.11 kg
Gross weight	0.14 kg
Shape of cut-out	round
Installation depth	11 cm
Installation diameter	5.5 cm

Accessories

1005609	LED Driver, 200 mA 10 W PHASE, Quick Connector
1005610	LED Driver, 200 mA 10 W, Quick Connector
1005611	LED Driver, 200 mA 13,5 W DALI dimmable, Quick Connector
1005612	NUMINOS® XS, diffuser
1005613	NUMINOS® XS, transparent diffuser
1005614	NUMINOS® XS, frosted diffuser
1005615	NUMINOS® XS, black diffuser
1006457	LED bridge driver, 12 W, 200 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour
1006457	LED bridge driver, 12 W, 200 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour