

# NUMINOS® XS

**black / chrome recessed ceiling light, 4000K 40°**

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1005540 |
| **IP Code** | IP 20 / IP 44 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 7 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 730 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Risk Group** | 2 |
| **Height** | 4.5 cm |
| **Diameter** | 6.5 cm |

| | |
|---|---|
| 798305 |  |

## Accessories

| | |
|---|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1005612 | NUMINOS® XS , diffuser |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector |
| 1005615 | NUMINOS® XS , black diffuser |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005613 | NUMINOS® XS , trans-parent diffuser |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

| | |
|---|---|
| **Net weight** | 0.115 kg |
| **Gross weight** | 0.135 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 11 cm |
| **Installation diameter** | 5.5 cm |
| **BIG WHITE Page** | 84 |