


NUMINOS® MOVE XS | DL

NUMINOS® MOVE XS, white/black recessed ceiling light, 4000 K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



Light source

798305	A G E

Item no.	1005606
Lamps included	No
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	55°
Color	white/black
CRI	90
UGR ≤	25
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	2
Height	5.5 cm
Diameter	8 cm
Net weight	0.15 kg
Gross weight	0.18 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm

Accessories

1005609	LED Driver, 200 mA 10 W PHASE, Quick Connector
1005610	LED Driver, 200 mA 10 W, Quick Connector
1005611	LED Driver, 200 mA 13,5 W DALI dimmable, Quick Connector
1005612	NUMINOS® XS, diffuser
1005613	NUMINOS® XS, transparent diffuser
1005614	NUMINOS® XS, frosted diffuser
1005615	NUMINOS® XS, black diffuser
1006135	Numinos® XS Reducing ring, round 160/70 mm black
1006136	Numinos® XS Reducing ring, round 160/70 mm white
1006137	Numinos® XS Reducing ring, square 160/70 mm black
1006138	Numinos® XS Reducing ring, square 160/70 mm white
1006457	LED bridge driver, 12 W, 200 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour