


NUMINOS® XL PD

PHASE, Pendant light, pendant length 250 cm, 2700 K, 28 Watt, 24°, trailing edge, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® PD, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 3550 lm and an impressive efficiency of 126.79 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1005705
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	54
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	700
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	54
Number of luminaires at LS C16A	54
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	3550 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	matt black
CRI	90

1411536	

Service life	50000 h
Risk Group	1
Height	25.8 cm
Diameter	12 cm
Pendant length	250 cm
Net weight	1.878 kg
Gross weight	2.192 kg
BIG WHITE Page	238