


# NUMINOS® XL 3Ph.

**PHASE, 3~ Spotlight, cylindrical, 3000 K, 28 Watt, trailing edge, 36°, matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 3550 lm and an impressive efficiency of 126.79 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1005730 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Primary nominal voltage** | 220-240AC50/60 Hz |
| **Secondary power / voltage** | 700 |
| **Safety class** | I |
| **Wattage** | 28 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 54 |
| **Number of luminaires at LS C16A** | 54 |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 50 µs |
| **Lumen** | 3550 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 36 ° |
| **Color** | matt black |
| **CRI** | 90 |
| **Service life** | 50000 h |

| | |
|---|---|
| 1411586 |  |

| | |
|---|---|
| **Risk Group** | 1 |
| **Length** | 25.8 cm |
| **Height** | 18.5 cm |
| **Diameter** | 12 cm |
| **Net weight** | 1.635 kg |
| **Gross weight** | 2.075 kg |
| **BIG WHITE Page** | 635 |