

NUMINOS® GIMBLE XS

white recessed ceiling light, 2700K 20°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1005823
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Lumen	670 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.15 kg
Shape of cut-out	round

798300	

Accessories

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006135	Numinos® XS Reducing ring , round 160/70mm black
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70mm black
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1006138	Numinos® XS Reducing ring , square 160/70mm white
1005613	NUMINOS® XS , trans-parent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	88