

# NUMINOS® GIMBLE XS

**black / chrome recessed ceiling light, 3000K 40°**

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1005836 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 7 W |
| **Lumen** | 700 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 5.7 cm |
| **Diameter** | 8 cm |
| **Net weight** | 0.13 kg |
| **Gross weight** | 0.15 kg |
| **Shape of cut-out** | round |

| | |
|---|---|
| 798303 |  |

## Accessories

| | |
|---|---|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1005612 | NUMINOS® XS , diffuser |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector |
| 1005615 | NUMINOS® XS , black diffuser |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white |
| 1005613 | NUMINOS® XS , trans-parent diffuser |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

| | |
|---|---|
| **Installation depth** | 8 cm |
| **Installation diameter** | 6.8 cm |
| **BIG WHITE Page** | 88 |