


NUMINOS® GIMBLE S | DL

NUMINOS® GIMBLE S, black / chrome recessed ceiling light, 3000 K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



Light source

791815	A G E

Item no.	1005893
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Secondary power / voltage	250 mA
Safety class	III
Wattage	9 W
Temperature at glass (light emission)	109
Beam angle	55°
Color	black/chrome
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	7 cm
Diameter	10 cm
Net weight	0.21 kg
Gross weight	0.25 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	9 cm

Accessories

1004786	NUMINOS® S, diffuser Ellipse
1004787	NUMINOS® S, diffuser Prisma
1004788	NUMINOS® S, diffuser Frosted
1004789	NUMINOS® S, diffuser Wabe
1004055	LED driver, 6.5-10 W 250 mA PHASE
1004058	LED driver, 6.5-10 W 250 mA
1004067	LED driver, 20 W 250 mA DALI
1006139	Numinos® S Reducing ring, round 160/90 mm black
1006140	Numinos® S Reducing ring, round 160/90 mm white
1006141	Numinos® S Reducing ring, square 160/90 mm black
1006142	Numinos® S Reducing ring, square 160/90 mm white
1006458	LED bridge driver, 12 W, 250 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour