

# NUMINOS® GIMBLE S

**white / chrome recessed ceiling light, 4000K 40°**

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1005917 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 250 mA |
| **Safety class** | III |
| **Wattage** | 8.6 W |
| **Lumen** | 750 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 7 cm |
| **Diameter** | 10 cm |
| **Net weight** | 0.2 kg |
| **Gross weight** | 0.24 kg |
| **Shape of cut-out** | round |

| | |
|---|---|
| 791831 |  |

## Accessories

| | |
|---|---|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black |

| | |
|---|---|
| **Installation depth** | 7 cm |
| **Installation diameter** | 9 cm |
| **BIG WHITE Page** | 88 |