

NUMINOS® GIMBLE L

white / black recessed ceiling light, 2700K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® GIMBLE L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1005990
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	25.4 W
Lumen	2150 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	11.5 cm
Diameter	16 cm
Net weight	0.6 kg
Gross weight	0.75 kg
Shape of cut-out	round

791800	

Accessories

1006148	Numinos® L Reducing ring , round 240/150mm white
1006149	Numinos® L Reducing ring , square 240/150mm black
1004062	LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006150	Numinos® L Reducing ring , square 240/150mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006147	Numinos® L Reducing ring , round 240/150mm black
1004070	LED driver , 40W 700mA DALI
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Installation depth	11.5 cm
Installation diameter	14.5 cm
BIG WHITE Page	89