

# NUMINOS® GIMBLE XL

**black / chrome recessed ceiling light, 3000K 55°**

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XL recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006055 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 1000/1050 mA |
| **Safety class** | III |
| **Wattage** | 37.4 W |
| **Lumen** | 3500 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 55 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 13.5 cm |
| **Diameter** | 19 cm |
| **Net weight** | 0.85 kg |
| **Gross weight** | 1 kg |
| **Shape of cut-out** | round |

| | |
|---|---|
| 791823 |  |

## Accessories

| | |
|---|---|
| 1006152 | Numinos® XL Reducing ring , round 240/180mm white |
| 1006151 | Numinos® XL Reducing ring , round 240/180mm black |
| 1004800 | NUMINOS® XL , diffuser Frosted |
| 1004071 | LED driver 4.2-50W 1050mA DALI |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006154 | Numinos® XL Reducing ring , square 240/180mm white |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004798 | NUMINOS® XL , diffuser Ellipse |
| 1006153 | Numinos® XL Reducing ring , square 240/180mm black |
| 1004059 | LED driverm 40W multi mA |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE |
| 1004801 | NUMINOS® XL , diffuser Wabe |
| 1004799 | NUMINOS® XL , diffuser Prisma |

| | |
|---|---|
| **Installation depth** | 13.5 cm |
| **Installation diameter** | 17.5 cm |
| **BIG WHITE Page** | 89 |