


# FLOODI S

**anthracite / transparent wall and ceiling-mounted light, 9.3 W 3000 K 100°**

High-output FLOODI spotlight for effective illumination of areas and squares. The swivelling mounting bracket and IP65 protection make the spotlight suitable for outdoor mounting on walls and ceilings. The spotlight is connected electrically through the existing cable connector on the casing itself.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006191 |
| **Rotating or tilting** | tiltable |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Safety class** | I |
| **Wattage** | 9.3 W |
| **Minimum ambient temperature** | -30 °C |
| **Maximum ambient temperature** | 35 °C |
| **Lumen** | 1040 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 100 ° |
| **Color** | anthracite |
| **CRI** | 80 |
| **Service life** | 40000 h |
| **Length** | 9.5 cm |
| **Width** | 2.8 cm |
| **Height** | 16 cm |
| **Net weight** | 0.217 kg |
| **Gross weight** | 0.305 kg |
| **BIG WHITE Page** | 1029 |

| | |
|---|---|
| 954790 |  |

## Accessories

| | |
|---|---|
| 1006326 | Sensor for FLOODI |