




OCULUS WL PHASE

Wall-mounted light black 8.5 W 570 lm 2000-3000 K CRI 90 100° Dimmable

Thanks to its special lens optics, the OCULUS WL PHASE wall-mounted light emits a sharply delineated beam of light. The lighting features a CRI of over 90 and a dim-to-warm function (2000-3000 K). Ideal for GP practices, law offices, cafés, hotels, restaurants and the private sector. In addition, the wall light can be quickly and easily connected to a 220 volt supply.



TECHNICAL DATA

Item no.	1006307
Number of different light outlets	1
IP Code	IP20
Dimmable	Yes
Dimming technology	Dim-to-Warm,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	8.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	2 A
Duration of inrush current	50 µs
Lumen	57-570 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	black
CRI	90
Service life	25000 h
Risk Group	1
Height	8.75 cm
Depth	12.4 cm

916398	

Diameter	9 cm
Net weight	0.681 kg
Gross weight	0.883 kg
BIG WHITE Page	385