



ENOLA OCULUS CL

Ceiling-mounted light anthracite 11 W 1000/1100 lm 3000/4000 K CRI 90 100°

Minimalist design with a sharply delineated light: the cylindrical ENOLA OCULUS CL uses special lens technology, which makes it the perfect accent lighting source. At the same time, this aluminium and glass ceiling light can withstand dirt and jets of water from all angles thanks to its IP65 protection class rating. The light colour (3000/4000 K) in this 1000 / 1100 lumen outdoor light can be adjusted using the CCT switch before installation. The ENOLA OCULUS CL also has impressive characteristics such as a CRI of over 90 and an installation panel (supplied with the light) that enables a quick connection to a 220 volt supply.

TECHNICAL DATA

Item no.	1006327
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Lumen	1000 / 1100 lm
Colour temperature	3000/4000 Kelvin
Beam angle	100 °
Color	anthrazit
CRI	90
Service life	30000 h
Risk Group	1
Height	12 cm
Diameter	10 cm

916566	

Accessories

1003479	Spacer set , for the ENO-LA SQUARE OUT and ROUND OUT ceiling lights in anthracite

Net weight	0.762 kg
Gross weight	0.954 kg
BIG WHITE Page	828