



ENOLA OCULUS WL

up/down wall-mounted light anthracite 20 W 1880/2120 lm 3000/4000 K CRI 90 100°

The cylindrical ENOLA OCULUS WL uses a special lens technology that creates a sharply delineated lighting effect. Thanks to its IP65 protection class rating, this aluminium and glass wall light is ideally protected in any weather. The CCT switch allows you to select the colour temperature in this 1880 / 2120 lumen light. The ENOLA OCULUS WL also has impressive characteristics such as a CRI of over 90 and an installation panel (supplied with the light) that enables a quick connection to a 220 volt supply.

TECHNICAL DATA

Item no.	1006329
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	37
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	300 µs
Lumen	1880 / 2120 lm
Colour temperature	3000/4000 Kelvin
Beam angle	100 °
Color	anthrazit
CRI	90
Service life	30000 h
Risk Group	1
Height	18 cm

916566	

Accessories

1002853	Spacer set , for outdoor wall-mounted lights anthracite

Depth	15.3 cm
Diameter	10 cm
Net weight	1.617 kg
Gross weight	1.902 kg
BIG WHITE Page	865