
# IN-LINE 44 48V TRACK

**opal, DALI, spot, white 14 W, 1180 lm, 3000 K, CRI 90, 95°**

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 95° beam angle in various lumen and natural colour reproduction (CRI >90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006624 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Primary nominal voltage** | 48DC |
| **Secondary power / voltage** | 350 mA |
| **Safety class** | III |
| **Wattage** | 14 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Lumen** | 1180 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 95 ° |
| **Color** | white |
| **UGR ≤** | 28 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 43.5 cm |
| **Width** | 2.2 cm |

| | |
|---|---|
| 2115947 |  |

| | |
|---|---|
| **Height** | 2.5 cm |
| **Net weight** | 0.29 kg |
| **Gross weight** | 0.351 kg |
| **BIG WHITE Page** | 525 |