


# NUMINOS® XS 48V TRACK

**DALI, pendant light, black / black, 8.7W, 700lm, 3000K, CRI90, 20°**

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006777 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP 20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly details** | Track,Track Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | DALI 2 |
| **Primary nominal voltage** | 48V |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 8.7 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Network rated standby power** | 0.5 W |
| **Lumen** | 700 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 16 |
| **LXXBXX data** | L80B50 |

| | |
|---|---|
| 798303 |  |

## Accessories

| | |
|---|---|
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005612 | NUMINOS® XS , diffuser |
| 1005615 | NUMINOS® XS , black diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |

| | |
|---|---|
| **Service life** | 50000 h |
| **Risk Group** | 2 |
| **Height** | 8 cm |
| **Diameter** | 5 cm |
| **Pendant length** | 150 cm |
| **Net weight** | 0.211 kg |
| **Gross weight** | 0.226 kg |
| **BIG WHITE Page** | 471 |