


NUMINOS DL, MOVE | DL, Move

NUMINOS® PROJECTOR M, recessed ceiling light, 2700 K, 40°, cylindrical, black / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700 K/3000 K/4000 K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



Item no.	1006980
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Secondary power / voltage	500 mA
Safety class	III
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	black/chrome
UGR ≤	22
LXXBXX data	L80B50
Risk Group	1
Length	13 cm
Diameter	8 cm
Net weight	0.76 kg
Gross weight	0.91 kg
Shape of cut-out	round
Installation depth	15 cm
Installation diameter	10.5 cm

Light source

791800	A G E

Accessories

1004790	NUMINOS® M, diffuser Ellipse
1004791	NUMINOS® M, diffuser Prisma
1004792	NUMINOS® M, diffuser Frosted
1004793	NUMINOS® M, diffuser Wabe
1004064	LED driver, 21-29.5 W 500/600/700 mA
1004054	LED driver, 20 W 500 mA PHASE
1004069	LED driver, 29 W 500 mA DALI
1006459	LED bridge driver, 42 W, 500 mA for NU-MINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour