





OVAL 14 WL

wall-mounted light 2700/3000 K, 6 W, black

Flat design, oval shape: the OVAL wall-mounted light available in black or white creates a real indoor feature. The light is distributed up and down the wall, illuminating it with a diffused glow that creates a sense of real comfort. The colour temperature can be adjusted between a warm white 2700 and 3000 Kelvin via a CCT switch prior to installation for added effect. In typical SLV fashion, it can be quickly and easily assembled and connected to a 230V mains voltage.



TECHNICAL DATA

Item no.	1007142
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Number of through-wires	74
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	145 mA
Safety class	I
Wattage	5.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0.72
Number of luminaires at LS B16A	74
Number of luminaires at LS C16A	123
Level of inrush current	13 A
Duration of inrush current	155 µs
Temperature at glass (light emission)	45 °C
Lumen	280 lm
Colour temperature	2700/3000 Kelvin
Color	black/frosted
CRI	80

1837788	

Service life	50000 h
Risk Group	1
Width	13.5 cm
Height	9 cm
Depth	3.1 cm
Net weight	0.51 kg
Gross weight	0.619 kg
BIG WHITE Page	853