

Set consisting of 12 x 1007095 UNIVERSAL DOWNLIGHT PHASE IP65 38° and 1007096 UNIVERSAL DOWN-LIGHT cover IP65 black R

The UNIVERSAL DOWNLIGHT Multipack contains 12 of the UNIVERSAL DOWNLIGHT PHASE recessed lights with matching covers in black. An all-round carefree package that makes planning even easier with our UNIVERSAL DOWNLIGHT. Due to its narrow beam angle of 38 degrees, the recessed light provides a targeted beam of light. The IP65 protection rating also protects it from water jets. The CCT switch allows the color temperature to be selected before installation (2700/3000/4000/6000K), giving you maximum flexibility on the construction site. The choice of total wattage - 5W or 8W - is just as easy. True-to-life colour reproduction is guaranteed thanks to CRI90. The corresponding Quick Connector Box rounds off the overall picture and makes installation of these recessed lights easier than ever.

TECHNICAL DATA

Item no.	1007271
IP Code	IP20/IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/90 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	60
Number of luminaires at LS C16A	150
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0
Lumen	560/610/680/640 lm
Colour temperature	2700/3000/4000/6500 Kelvin

1807465	

Beam angle	38 °
Color	black
CRI	90
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Risk Group	0
Height	4.85 cm
Diameter	8.8 cm
Net weight	3 kg
Gross weight	3.21 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	208