




# LID II

**wall-mounted light, 2700/3000 K, 15 W, PHASE, 100°, anthracite**

Adjustable light colour via CCT switch (2700 K/3000 K), a colour rendering index of over 80 and a long LED lifespan of 50,000 hours: the new LID II wall light emits a powerful light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007282 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 20 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 350 mA |
| **Safety class** | I |
| **Wattage** | 15 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 71 |
| **Number of luminaires at LS C16A** | 89 |
| **Level of inrush current** | 6.5 A |
| **Duration of inrush current** | 40 µs |
| **Temperature at glass (light emission)** | 63 °C |
| **Lumen** | 800/800 lm |
| **Colour temperature** | 2700/3000 Kelvin |
| **Beam angle** | 100 ° |
| **Color** | anthracite |

| | |
|---|---|
| 1807466 |  |

| | |
|---|---|
| **CRI** | 80 |
| **Service life** | 48000 h |
| **Risk Group** | 1 |
| **Depth** | 6.5 cm |
| **Diameter** | 22 cm |
| **Net weight** | 0.843 kg |
| **Gross weight** | 1.138 kg |
| **BIG WHITE Page** | 847 |