


# NEW TRIA® 68

**recessed ceiling light, 2700 K, 38°, IP 20, round, white**

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700 K/3000 K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007385 |
| **Rotating or tilting** | tiltable |
| **IP Code** | IP20 |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | II |
| **Wattage** | 8.3 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 88 |
| **Number of luminaires at LS C16A** | 149 |
| **Level of inrush current** | 3 A |
| **Duration of inrush current** | 30 µs |
| **Lumen** | 705 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 38 ° |
| **Color** | white |
| **Risk Group** | 1 |
| **Height** | 4 cm |
| **Diameter** | 8.2 cm |

| | |
|---|---|
| 869193 |  |

| | |
|---|---|
| **Net weight** | 0.204 kg |
| **Gross weight** | 0.246 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 4 cm |
| **Installation diameter** | 6.8 cm |
| **BIG WHITE Page** | 105 |