

# NEW TRIA®

**LED module, round, 2700 K, 60°, PHASE, black**

Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. The 12 W LED MODULE is a modular element and fits the New Tria 95 recessed rings and is available with different light colours (2700 K/3000 K) and beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI >90 make this an exceptional quality product. In addition, the NEW TRIA® LED MODULE is impressive because of its service life of L80B10@50,000h.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007411 |
| **IP Code** | IP20 |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 350 mA |
| **Safety class** | II |
| **Wattage** | 13.3 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 85 |
| **Number of luminaires at LS C16A** | 144 |
| **Level of inrush current** | 2 A |
| **Duration of inrush current** | 80 µs |
| **Lumen** | 1130 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 60 ° |
| **Color** | white |
| **CRI** | 90 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 5 cm |

| | |
|---|---|
| 869219 |  |

## Accessories

| | |
|---|---|
| 1007448 | NEW TRIA® 95 , ceiling installation ring, L: 11 W: 11 H: 2.6 cm, IP 20, white |
| 1007443 | NEW TRIA® 95 , ceiling installation ring, D: 11 H: 2.6 cm, IP 20, white |
| 1007454 | NEW TRIA® 95 , ceiling installation ring, recessed, D: 10.3 H: 5.5 cm, IP 20, white |

| | |
|---|---|
| **Diameter** | 7 cm |
| **Net weight** | 0.228 kg |
| **Gross weight** | 0.261 kg |
| **BIG WHITE Page** | 125 |