

NEW TRIA®

LED module, round, 3000 K, 60°, PHASE, black

Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. The 12 W LED MODULE is a modular element and fits the New Tria 95 recessed rings and is available with different light colours (2700 K/3000 K) and beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI >90 make this an exceptional quality product. In addition, the NEW TRIA® LED MODULE is impressive because of its service life of L80B10@50,000h.

TECHNICAL DATA

Item no.	1007412
IP Code	IP20
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	13.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	85
Number of luminaires at LS C16A	144
Level of inrush current	2 A
Duration of inrush current	80 µs
Lumen	1200 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
Service life	50000 h
Risk Group	1
Height	5 cm

869646	

Accessories

1007448	NEW TRIA® 95 , ceiling installation ring, L: 11 W: 11 H: 2.6 cm, IP 20, white
1007443	NEW TRIA® 95 , ceiling installation ring, D: 11 H: 2.6 cm, IP 20, white
1007454	NEW TRIA® 95 , ceiling installation ring, recesse-d, D: 10.3 H: 5.5 cm, IP 20, white

Diameter	7 cm
Net weight	0.228 kg
Gross weight	0.261 kg
BIG WHITE Page	125